

# GS# 79

## Material Safety Data Sheet



### Section 1

Product and Company Identification

<b>Product Name:</b>	GS# 79
<b>Product Description:</b>	Extruded Tape Sealant
<b>Manufacturer:</b>	General Sealants, Inc. 300 S. Turnbull Canyon Road, City of Industry, CA 91745
<b>Information Phone:</b>	626-961-0211 FAX: 626-968-5140
<b>Web Site:</b>	www.generalsealants.com
<b>Emergency Phone:</b>	626-961-0211 or 800-762-1144
<b>Issue Date:</b>	9/01/2009

### Section 2

Composition/Information on Ingredients

No reportable hazardous substances or complex substances.

### Section 3

Hazards Identification

This material is not considered to be hazardous according to regulatory guidelines (see Section 15).

### Section 4

First Aid Measures

<b>Eye Contact:</b>	Flush with warm water for 15 minutes. If irritation persists, seek medical attention.
<b>Skin Contact:</b>	Wash contaminated area with soap and water for 15 minutes. If irritation persists, seek medical attention.
<b>Ingestion:</b>	Do not induce vomiting. Seek medical attention.
<b>Inhalation:</b>	Remove to fresh air. Seek medical attention.

# GS# 79

## Material Safety Data Sheet



### Section 5

#### Fire Fighting Measures

<b>Flash Point:</b>	N/A
<b>Auto Ignition Point:</b>	N/A
<b>Lower Explosive Limit:</b>	N/A
<b>Upper Explosive Limit:</b>	N/A
<b>Extinguishing Media:</b>	Use water spray (fog), foam, dry chemical or carbon dioxide (CO2).
<b>Fire Fighting Instructions:</b>	Use water spray to cool fire exposed surfaces. Use standard protective equipment and in enclosed spaces a self contained breathing apparatus.
<b>Fire And Explosion Hazards:</b>	Irritating gases may be present.

### Section 6

#### Accidental Release Measures

Avoid release to the environment. Contain spill, collect, and transfer to suitable containers. Do not flush to sewer or allow to enter waterways. Recycle or dispose in accordance with federal, state, and local regulations.

### Section 7

#### Handling and Storage

<b>Handling and Storage Precautions:</b>	Store in closed containers at 72° F. Avoid excessive heat. For industrial use only.
--	---

### Section 8

#### Exposure Controls/Personal Protection

<b>Engineering Controls:</b>	Use with adequate general ventilation.
<b>Eye/face Protection:</b>	N/A
<b>Skin Protection:</b>	Use gloves when material is hot.
<b>Respiratory Protection:</b>	N/A
<b>Other/ General Protection:</b>	Wash thoroughly after handling.

N/A= Not Applicable

# GS# 79

## Material Safety Data Sheet



### Section 9

Physical and Chemical Properties

<b>Appearance:</b>	Gray
<b>Odor:</b>	No Odor
<b>Chemical Type:</b>	Mixture
<b>Physical State:</b>	Solid
<b>Melting Point:</b>	N/A
<b>Boiling Point:</b>	N/A
<b>Specific Gravity (Water=1):</b>	1.54
<b>Vapor Pressure:</b>	N/A
<b>Vapor Density (Air=1):</b>	N/A
<b>Solubility in Water:</b>	Insoluble
<b>Evaporation Rate (n-butyl Acetate=1):</b>	N/A

### Section 10

Stability and Reactivity

<b>Stability:</b>	Stable
<b>Hazardous Polymerization:</b>	Will not occur
<b>Incompatible Materials:</b>	Strong oxidizing agents
<b>Hazardous Decomposition Products:</b>	Thermal decomposition may form carbon dioxide, carbon monoxide and various hydrocarbon fumes.
<b>Condition to avoid:</b>	None known

### Section 11

Toxicological Information

No data available

N/A= Not Applicable

# GS# 79

## Material Safety Data Sheet



### Section 12

Ecological Information

No data available

### Section 13

Disposal Consideration

Dispose in accordance with applicable federal, state and local government regulations.

### Section 14

Transportation Information

Proper Shipping Name  
Not regulated by the USDOT

### Section 15

Regulatory Information

When used for its intended purposes, this material is not classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

### Section 16

Other Information

<b>NFPA Rating:</b>	Health:0 Flammability:0 Reactivity:0
<b>HMIS Rating:</b>	Health:0 Flammability:0 Reactivity:0

#### USER'S RESPONSIBILITY

THIS PRODUCT INFORMATION CANNOT COVER ALL POSSIBLE SITUATIONS, WHICH THE USER MAY EXPERIENCE DURING PROCESSING. EACH ASPECT OF YOUR OPERATION SHOULD BE EXAMINED TO DETERMINE IF, OR WHERE, ADDITIONAL PRECAUTIONS MAY BE NECESSARY. ALL HEALTH AND SAFETY INFORMATION CONTAINED IN THIS BULLETIN SHOULD BE PROVIDED TO YOUR EMPLOYEES OR CUSTOMERS. IT IS YOUR RESPONSIBILITY TO USE THIS INFORMATION TO DEVELOP APPROPRIATE WORK PRACTICE GUIDELINES AND EMPLOYEE INSTRUCTIONAL PROGRAMS FOR YOUR OPERATION.

#### DISCLAIMER OF LIABILITY

AS THE CONDITIONS OR METHODS OF USE ARE BEYOND OUR CONTROL, WE DO NOT ASSUME ANY RESPONSIBILITY AND EXPRESSLY DISCLAIM ANY LIABILITY FOR ANY USE OF THIS MATERIAL. INFORMATION CONTAINED HEREIN IS BELIEVED TO BE TRUE AND ACCURATE BUT ALL STATEMENTS OR SUGGESTIONS ARE MADE WITHOUT WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OF THE INFORMATION, THE HAZARDS CONNECTED WITH THE USE OF THE MATERIAL OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS REMAINS THE RESPONSIBILITY OF THE USER.

#### CONFIDENTIALITY NOTICE

THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION BELONGING TO THE SENDER, WHICH IS LEGALLY PRIVILEGED. THE INFORMATION IS INTENDED ONLY FOR THE USE OF THE INDIVIDUAL OR ENTITY NAMED ABOVE. IF YOU ARE NOT THE INTENDED RECIPIENT, BE AWARE THAT ANY DISCLOSURE, COPYING, DISTRIBUTION OR USE OF THIS INFORMATION IS PROHIBITED. IF YOU HAVE RECEIVED THIS IN ERROR, PLEASE CONTACT US IMMEDIATELY AND DELETE (DESTROY) THE DOCUMENT.

#### WARRANTY

PRODUCTS ARE SOLD WITHOUT WARRANTY, EXPRESSED OR IMPLIED, EXCEPT IF SHOWN TO BE DEFECTIVE IN MATERIALS WITHIN 30 DAYS OF SHIPMENT BY US, IT WILL BE REPLACED OR AT OUR OPTION THE PURCHASE PRICE WILL BE REFUNDED TO THE PURCHASER. WE ASSUME NO RESPONSIBILITY FOR CONSEQUENTIAL DAMAGE ARISING FROM THE USE OF OUR PRODUCTS. USER MUST CONFIRM THE ADAPTABILITY OF OUR PRODUCTS BY THEIR OWN TEST. NO REPRESENTATIVE OF OUR COMPANY OR ANY OTHER HAS AUTHORIZATION TO GRANT ANY ADDITIONAL WARRANTY.

GENERAL SEALANTS, INC. 300 S. Turnbull Canyon Rd. / City of Industry, CA 91745 / P.O. Box 3855 / City of Industry, CA 91744  
(626) 961-0211 • (800) 762-1144 • Fax: (626) 968-5140  
E-Mail: [sticktoquality@generalsealants.com](mailto:sticktoquality@generalsealants.com) • [www.generalsealants.com](http://www.generalsealants.com)